

COMPACT, LIGHTWEIGHT, EASY-TO-USE

TRANSCAT

▶ Visit us at Transcat.com!

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001



Both Proheat Models offer the following features:

- **Built-in hand and switch guard**
- **Oil-resistant, grounded Neoprene 3-wire cordset**
- **Double-protected element housing**
- **Wrap-around air intake which allows gun to draw in air while in the upright position**
- **Accessory attachments for versatility**
- **Hanging loop for assembly line use**
- **Made in U.S.A**

This heat gun with temperature settings of 570° and 1050° F (299 and 565° C); and airflow of 15 CFM at 3650 FPM meets the requirements of most materials. The variety of attachments available makes the Proheat heat gun adaptable for a wide variety of uses including aircraft and marine applications.

The Proheat features a DC permanent magnet motor that is compatible with all electrical frequencies. The compact, ergonomically-designed Lexan® * housing, enclosed ceramic heating element and wrap-around air intake assure you of a lightweight (1 lb. 10 oz.), easy-to-use source of flameless heat

whether you're working with shrinkable packaging materials, spot-drying paint, bending plastics/laminates or activating adhesives.

*Registered Trademark of General Electric

ORDERING INFORMATION AND SPECIFICATIONS

MODEL-NO.	APPROX TEMP NOZZLE	APPROX TEMP NOZZLE	VOLTS	AMPS	WATTS	Hz.
-----	°F	°C	-----	-----	-----	-----
PH-1100-Proheat Heat Gun	570	299	120	6	750	50-400
	1050	565	120	12	1500	50-400
PH-2100-Proheat Heat Gun	570	299	220	3	750	50-400
	850	455	220	6	1300	50-400

- Overall dimensions: 8.25" L x 3.0" W x 7.3" H
- Nozzle opening diameter - 1.3"
- Net weight 1 lb. 10 oz.
- Shipping weight 2 lbs.
- Cord length - 6 ft.

Available accessories are designed to be used with both the Proheat Heat Gun and the Proheat Varitemp Heat Gun.

Note: 240V not available.

TRANSCAT

[▶ Visit us at Transcat.com!](http://Transcat.com)

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001