

Additel 680

Digital Pressure Gauges

- Pressure ranges to 10,000 psi (700 bar)
- 0.25%FS accuracy
- Fully temperature compensated accuracy
- IP67
- Data logging and wireless (Optional model)

NEW



Gauge pressure

CE FC



680 with rubber boot (Optional)

OVERVIEW

With advanced microprocessor technology and state-of-the-art silicon pressure sensors, the 680 series digital pressure gauges provide an accurate, reliable, and economic solution for a wide range of pressure applications. They are loaded with functionality and remarkably easy to use. To reach the best performance, every silicon pressure sensor in our gauges is specially aged, tested and screened before assembly. With data logging and wireless features, the 680W gauge can store pressure measurement data in the internal memory or display them on PC through wireless communication. The 680 series digital pressure gauges are unmatched in performance and reliability. Best of all, they are very affordable.

FEATURES

- Pressure ranges to 10,000 psi (700 bar)
0.25% full scale accuracy
- Fully temperature compensated accuracy
from 14°F to 122°F (-10°C to 50°C)
- Up to 13 selectable pressure units, 6 customized
definition engineering units
- Large, easy to read display with 5-digit resolution
- Backlit display
- Icon-based menu
- Display flash warning when pressure exceeds
120% of FS
- Stainless wetted surface construction
- IP67 (submersible in 1 meter of water)
- Drop-tested from 1 meter
- 2 AA alkaline batteries
- CE RTTE, FCC ID, IC ID Certificates
- NIST traceable calibration with data(included)

SPECIFICATIONS

- **Model**
ADT680: Regular version
ADT680W: Data logging and wireless version
Pressure Type: Gauge
- **Performance**
Accuracy: 0.25%FS
Update Rate: 10 times/Sec ,3 times /Sec (default),
1 time /Sec ,1 time/15 Seconds
Operating Temperate: 14°F to 122°F (-10°C to 50°C)
Compensated Temperate: 14°F to 122°F (-10°C to
50°C), accuracy Guaranteed
Storage Temperature: -4°F to 158°F (-20°C to 70°C)
Overload Pressure: 1.2X
- **Power Supply**
Battery: 2 x AA alkaline (LR6) batteries
Recommend: Duracell MX1500, EnergizerE91,
Panasonic LR6, Duracell 15AU
Usage Period:
10/Sec:1500Hours; 3/Sec: 3000Hours;
1/Sec: 6000Hours; 1/15Sec: 12000Hours
Rated Power: 3.0VDC I_{max}=30mA P_{max}=90mW
- **Material**
Wetted Surface: All wetted surfaces are 316L
Stainless Steel with welded design (no O-ring,
thread tape, epoxy, or sealant on any part of the
sensor assembly)
Case: PC+ABS
Protective Cover: Silicone Rubber (Optional)

SPECIFICATIONS

- Display**
 LCD Specification: FSTN-LCD, Visual scope
 36x61mm; Full 5 digits, 15.2mm High; 7 segment
 analog bar graph scaled from 0~100% of FS
 Backlight: White
- Wireless Communication (ADT680W only)**
 Wireless Frequency: 2.4G ISM Bands, 20 meter
 range
 Number of wireless Channels : Chanel 1~15
 Software: Wireless network demo software for free
- Data Logging (ADT680W only)**
 Storage Capacity: 140,000 readings(time, pressure,
 and temperature)
 Storage Interval: Adjustable from 1~9999 Sec
- Compliances**
 Certificates: CE RTTE, FCC ID, IC ID
 Protection Level: IP67
 Vibration: 5g(20~2000Hz)
 Shock resistance: 100g/11ms
- Others**
 Dimensions: 100mm x 40mm, total height: 157mm
 Weight: 500g
 Fitting: 1/4NPT, G1/4, M20x1.5, or custom-made
- Auto off:**
 Disabled, 15, 30, 45, 60, 90, 120 Minutes optional.
- Filtering:** Averaging (3 to 10 samples) or low-pass
 first-order filter.


- Engineering units:** Pa, kPa, MPa, bar, mba, psi, kgf/
 cm², mmH₂O, mmHg, inH₂O, inHg, ozf/in, %, °C, °F.
 extend units: inH₂O(20°C), inH₂O(60°F), mmH₂O(20°C),
 mmH₂O(15°C), ftH₂O(60°F), ftH₂O(4°C)
- Backlight Duration:**
 Not auto off, 15, 30, 45, 60 seconds optional.
- Max/Min data capture:** Saves Max and Min data during
 pressure measurement.
- Key Lockout:** When the gauge is in auto-storing mode,
 the front panel buttons will be automatically locked.
- Overpressure Alarm:** Display will flash over 120%FS
- Battery voltage Indicator:** Displays the battery life
 remaining. When the battery voltage is too low, the
 gauge will power-off automatically.
- Overpressure Record:**
 Gauge will record max pressure data when the gauge is
 over pressured by 120% of FS.
- Leakage test:**
 In leak test mode, the gauge will record beginning
 pressure, ending pressure, and show the difference ΔP .
- Factory Reset:**
 Resets all settings back to factory default, except the
 calibration parameters.
- Warranty:** 1 year

Gauge Pressure				
P/N	Pressure Range (psi) ^[1]	Pressure Range (bar)	Media ^[1]	Burst Pressure
V15	-15	-1.0	G	3X
GP15	15	1.0	G,L	3X
GP30	30	2.0	G,L	3X
GP100	100	7.0	G,L	3X
GP300	300	20	G,L	3X
GP500	500	35	G,L	3X
GP1K	1,000	70	G,L	3X
GP3K	3,000	200	G,L	3X
GP5K	5,000	350	G,L	3X
GP10K	10,000	700	G,L	3X

Note: [1]. Sealed gauge pressure for above 1000 psi
 [2]. G=Gas, L=Liquid (please specify media type when place order)

ORDERING INFORMATION

Model Number



Accessories included

- AA battery (2 pcs)
- Manual
- NIST traceable calibration certificate

Optional Accessories

Model number	Description
9253	Rubber boot for Additel 680 gauge