

TESTEQUITY® Environmental Chambers

TestEquity Model 1007C Temperature Chamber - Detailed Specifications

[<< Back to Product Page](#)

Temperature Range	-73°C to +175°C
Control Tolerance	±0.2°C (Measured at the control sensor after stabilization)
Uniformity	±0.5°C (Variations throughout the chamber after stabilization)

Cool Down Transition Time*						
Start Temp	End Temp					
	+23°C	0°C	-40°C	-55°C	-65°C	-73°C
+23°C	----	4 min	18 min	25 min	33 min	Ultimate
+50°C	5 min	11 min	27 min	36 min	45 min	Ultimate
+85°C	13 min	20 min	37 min	47 min	55 min	Ultimate
+150°C	32 min	39 min	58 min	65 min	76 min	Ultimate

Heat Up Transition Time*						
Start Temp	End Temp					
	+23°C	+50°C	+85°C	+125°C	+150°C	+175°C
+23°C	----	1.5 min	7 min	14 min	20 min	Ultimate
0°C	1.5 min	3.5 min	13 min	20 min	23 min	Ultimate
-40°C	6 min	11 min	17 min	24 min	30 min	Ultimate
-55°C	8 min	13 min	19 min	26 min	32 min	Ultimate
-65°C	10 min	14 min	21 min	28 min	34 min	Ultimate

Rate Of Change

To calculate rate of change for a particular condition, take the difference between the Start Temp and End Temp and divide by the Transition Time.


Cool Down Example: From +50°C to -40°C = 90°C / 27 min = 3.33°C/min.

Heat Up Example: From -40°C to +50°C = 90°C / 11 min = 8.18°C/min.

*Note: Transition times are measured after a 2 hour soak at the respective start temperature with an empty chamber, as indicated on the temperature controller, 23°C ambient. Measured with setpoint beyond the start and end temperatures. Does not include the effect of proportional band when approaching setpoint. Performance is reduced by 17% with 50 Hz input power.

Live Load Capacity				
+23°C	0°C	-40°C	-55°C	-65°C
1,000 Watts	800 Watts	500 Watts	400 Watts	300 Watts

Refrigeration and Heating System	
High Stage Refrigerant	R-404A (Dupont HP-62)
Low Stage Refrigerant	R-508B (Dupont SUVA-95)
Compressors	1.5 HP x 1.5 HP Tecumseh hermetic compressors in a cascade configuration.
Condenser	Air Cooled

Heat of Rejection	14,800 BTUH (maximum rated chamber load at maximum cooling rate from high temperature soak)	
Heater Power	2,000 Watts	
Instrumentation		
Temperature Controller	Watlow F4 Controller with RS-232 interface, LED readout of temperature, LCD display of other parameters (standard). Watlow F4T Touch Screen Controller with RS-232, Ethernet interface, 4.3" color graphic touch screen (optional).	
Chart Recorder	(Optional) Honeywell DR4300 Series. One pen, 10" circular chart. Mounts in lower front door.	

Input Power Requirements			
	Phase	Current Draw	Minimum Service
230 V ±10%, 60 Hz	1 PH	25 A	30 A
	3 PH	19 A	25 A
208 V -5/+10%, 60 Hz	1 PH	28 A	35 A
	3 PH	21 A	30 A

Input may be configured for single or three phase in the field by changing jumpers. Three phase load is semi-balanced. Call for 50 Hz operation. Cooling performance is reduced 17% at 50 Hz.

Customer power source must be hard-wired to the chamber by a qualified electrician. Power cord and plug is not included.

Physical Characteristics	
Inside Dimensions	24" W x 21" H x 24" D (7 cubic feet) 609 mm W x 533 mm H x 609 mm D (198 liters)
Outside Dimensions*	33" W x 67.75" H x 54.25" D (nominal) 838 mm W x 1721 mm H x 1378 mm D * Door latch adds 3" to width on right side (may be removed to permit move-in through a 36" doorway). Circulator motor and housing adds 6" to height.
Minimum Installed Clearance	18" from the left and right side 24" from the rear
Window Viewing Area	13.375" W x 9" H
Access Ports	4" Port on left and right side (two total) Supplied with foam plugs
Weight	Chamber Weight: 850 pounds Shipping Weight: 1,011 pounds
Sound Level	62 dBA in cooling mode (A-weighted, measured 36" from the front or side surface, 63" from the floor, in a free-standing environment)

NOTE: Performance is typical and based on operation at 23°C (73°F) ambient and nominal input voltage. Designed for use in a normal conditioned laboratory. Operation at higher ambient temperatures may result in decreased cooling performance. Additional ports and shelves will also affect performance. Operation above 30°C (85°F) or below 16°C (60°F) ambient is not recommended.

1 - 800 - 950 - 3457
International: 805-498-9933 Fax: 805-498-3733

[[Home](#)] [[Contact Us](#)]