



Simplicity Allows for Ease of Use

TX10 Series of Digital Thermometers

TX10 Series offers thermocouple thermometers that support K, J, E and T type thermocouples. There are three models available: 1-channel single-function, 1-channel multi-function, and 2-channel multi-function models.

**TX10
-01**



1-channel Single-function Model (TX10-01)

TC TYPE

Select the thermocouple type (K, J, E, and T) for the initial setting.
(The type K is factory-set at shipment)

Operation

Press and hold down the TC TYPE key while pressing the POWER key.
The TX10 enters the thermocouple type selection mode, and each press of the TC TYPE key switches between the thermocouple types.
Then accept the setting with the POWER key.
(Make sure that the characters in the display have changed.)

DATA HOLD

Press this key to hold the measured value.

Multi-function Models (TX10-02/-03)

Memory-in Function

Up to ten data items can be stored. When recalled, the stored data value is displayed with its memory number.

User calibration function

Calibration and adjustment can be made easily by operating the panel keys on instrument and a measurement-standard.

**TX10
-02/-03**



TC TYPE

Thermocouple type (K, J, E, and T) select key
(Operation is the same as TX10-01)

CH

(TX10-03 only)

Input channel select key
With each press, the channel switches through the sequence of "chA," "chB," and then "chA-chB."

DATA HOLD

Data hold key
A held measured value, can be stored in the memory of an optional memory number, which is selected with the ▲, ▼ keys.

RECORD

Maximum and minimum record key
Stores the maximum and minimum values from the time the RECORD key is pressed.

Data record key
Stores the held measured value in memory. (Up to ten)

RANGE

Resolution select key
With each press, resolution alternates between 0.1°C and 1°C.
(Within the range of -200.0°C to 199.9°C)

READ

Maximum and minimum values, and stored data read key
Every time this key is pressed, the maximum and minimum values, stored data, and the current measured data are displayed in sequence.

REL/ADJ

Relative display select key
Displays measured values with reference to the value obtained immediately before this key was pressed (relative value). Each press of this key can select or release the relative display.

Simplified correction mode key
Sets the correction value, and selects active/inactive of the simplified correction function.

▲, ▼ Data call-up key
Used to select a memory number when calling up stored data. Also used to adjust the correction value for simplified correction mode.

Light
Weight:
180 g

(Shown above is the TX10-03. The TX10-02 has no CH key.)

Can Be Used in Wide Variety of Applications



● Temperature management in a refrigerated warehouse




● Frozen food products quality control




● Perishable foods quality control



● Temperature management in production processes



● Product temperature measurement test



● Temperature checks in equipment maintenance
● Temperature management for research and development

Product name	Digital Thermometer		
	Single-function, 1 channel	Multi-function, 1 channel	Multi-function, 2 channels
Model	TX10-01	TX10-02	TX10-03
Number of input channels	1		2
Measuring range (only the main unit)	Thermocouple type Type K: -200°C to 1372°C [-328°F to 2501.6°F] Type J: -200°C to 1000°C [-328°F to 1832°F]	Type E: -200°C to 700°C [-328°F to 1292°F] Type T: -200°C to 400°C [-328°F to 752°F]	
Resolution	-200.0°C to 199.9°C: 0.1°C 200°C or above: 1°C	-200.0°C to 199.9°C: 0.1°C or 1°C (when 1°C resolution is set) +200°C or above: 1°C	
Accuracy (only the main unit)	-200.0°C to -100.1°C: -100.0°C to 199.9°C: +200°C or above, or when 1°C resolution is set:	±(0.1% of rdg + 1.0°C) ±(0.1% of rdg + 0.7°C) ±(0.2% of rdg + 1°C)	*Accuracy of reference junction compensation is included ±0.4°C when the temperature of the input terminal is in equilibrium.
Temperature coefficient	±(0.015% of rdg + 0.06°C)/°C		
Measurement interval	Approx. 1 sec.		Approx. 1 sec. (1 channel measurement) Approx. 2 sec. (2 channel measurement)
Data storage	None	Capable of storing up to 10 measured data items	
Simplified correction	None	Correction range: ±20°C of measured value	
Display items	HOLD, °C, ch A, TC type K, J, E, T, Battery alarm	HOLD, RCD, REL, ADJ, MAX, MIN, MEM, °C chA, TC type K, J, E, T Battery alarm	HOLD, RCD, REL, ADJ, MAX, MIN, MEM, °C chA, chB, chA-chB TC type K, J, E, T Battery alarm
Other functions	Auto power-off, battery alarm		
Display	LCD		
Operating temperature and humidity	0°C to 50°C, 20 to 80% RH (no condensation)		
Power requirements	Two AA-size alkaline dry batteries (LR6)		
Battery life	About 450 hours		
Drip-proof construction	Conforms to IP54 (dust-proof and drip-proof requirements of IEC529)		
Compliance with standards	EMC standards	EMI (interference signal): EN55011;1998, EN61326-1;1998+A1 (Class B, Group 1) EMS (immunity): EN50082-1;1997, EN61326;1998+A1	
External dimensions	<p style="text-align: center;">Approx. 151(H) × 56(W) × 33(D) mm (excluding protrusions) Weight: Approx. 180 g (including batteries)</p>		
Supplied accessories	Two AA-size alkaline dry batteries (LR6) and instruction manual		
Optional accessories	Temperature probes (for K type thermocouple) Rounded end probe (900 20, 900 21, 900 22) Needle probe (900 23, 900 24) Surface probe (900 30, 900 31, 900 32, 900 33) Bead TC (2459 07) Extension cable 5 m (2459 21) /10 m (2459 22) Soft case (930 12) Waterproof cover (5-per package) (930 11)		